



**concens**   
 member of **Bansbach** group  
 Oddesundvej 1 Phone: +4570111131  
 DK-6715 Esbjerg N Mail: Info@concens.com  
 Denmark Web: www.concens.com

**Proprietary and confidential**

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

**Concens Part No.:**

350150-143130-030000

Creation Date:

16-01-2026

Sheet size:

A4

**Comments:**

DIMENSIONS ARE IN mm,  
 TOLERANCE ON DIMENSIONS CAN  
 BE FOUND ON DATASHEET. OUT-OF-  
 SCALE TECHNICAL DRAWING.

**Configuration List:**

Stroke length: 150 mm  
 Rod position: 0 mm  
 Noise reduction: standard (Standard)  
 Gearing: 1:14-400 N (nominal)  
 Voltage: 24 VDC 1:14 (400N - 16mm/s)  
 Pitch: Nut /magnets (Includes AISI actuator tube (painted))  
 Cable length: 3 m  
 Cable Type and Connector: Black, no connector  
 Controller/Hall: Without hall sensor (Standard)  
 Steel/IP: Std. steel, IP66  
 Brackets: Alu w/clevis  
 Tube color: Black, RAL9005, shine 25 (Standard)  
 Ring color: Black (Standard)  
 Length: 320 mm