



concens 
member of **Bansbach** group

Oddesundvej 1
DK-6715 Esbjerg N
Denmark

Phone: +4570111131
Mail: Info@concens.com
Web: www.concens.com

Proprietary and confidential

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

Concens Part No.:

600250-813456D940200

Creation Date:
04-05-2026

Sheet size:
A4

Comments:

DIMENSIONS ARE IN mm,
TOLERANCE ON DIMENSIONS CAN
BE FOUND ON DATASHEET. OUT-OF-
SCALE TECHNICAL DRAWING.

Configuration List:

Stroke length: 250 mm
Rod position: 0 mm
Noise reduction: standard (Standard)
Gearing: 1:81-8100 N (nominel)
Voltage: 24 VDC
Pitch: 4mm std. (Standard)
Cable length: 5 m
Cable Type and Connector: Black shielded cable, no connector (Shielded cable is not available for EN/ES60601)
Controller/Hall: icon SPP D
Steel/IP: Std. steel, Harsh Env.
Brackets: AISI316
Tube color: Black, RAL9005, shine 25
Ring color: Black std. steel (Harsh E.)
Length: 648 mm