



**concens** 

member of **Bansbach** group

Oddesundvej 1  
DK-6715 Esbjerg N  
Denmark

Phone: +4570111131  
Mail: Info@concens.com  
Web: www.concens.com

**Proprietary and confidential**

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

**Concens Part No.:**

350150-143237A920000

Creation Date:  
19-06-2026

Sheet size:  
**A4**

**Comments:**

DIMENSIONS ARE IN mm,  
TOLERANCE ON DIMENSIONS CAN  
BE FOUND ON DATASHEET. OUT-OF-  
SCALE TECHNICAL DRAWING.

**Configuration List:**

Stroke length: 150 mm  
Rod position: 0 mm  
Noise reduction: standard (Standard)  
Gearing: 1:14-400 N (nominal)  
Voltage: 24 VDC 1:14 (400N - 16mm/s)  
Pitch: 2 mm std. (Standard)  
Cable length: 3 m  
Cable Type and Connector: Black shielded cable, Molex Minifit Jr. Connector (Shielded cable is not available for EN/ES60601)  
Controller/Hall: icon SDB A  
Steel/IP: Std. steel, Harsh Env.  
Brackets: Alu  
Tube color: Black, RAL9005, shine 25 (Standard)  
Ring color: Black std. steel (IP68)  
Length: 331 mm