



**concens**   
member of **Bansbach** group

Oddesundvej 1  
DK-6715 Esbjerg N  
Denmark

Phone: +4570111131  
Mail: [Info@concens.com](mailto:Info@concens.com)  
Web: [www.concens.com](http://www.concens.com)

**Proprietary and confidential**

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

**Concens Part No.:**

500750+173352-950200

**Creation Date:**

10-04-2026

**Sheet size:**

A4

**Comments:**

DIMENSIONS ARE IN mm,  
TOLERANCE ON DIMENSIONS CAN  
BE FOUND ON DATASHEET. OUT-OF-  
SCALE TECHNICAL DRAWING.

**Configuration List:**

Stroke length: 750 mm  
Rod position: 0 mm  
Noise reduction: low noise  
Gearing: 1:17-2200 N (nominal)  
Voltage: 24 VDC 1:17 (2200N - 17mm/s)  
Pitch: 3 mm std. (Standard)  
Cable length: 5 m  
Cable Type and Connector: Black, Molex Minifit (Standard)  
Controller/Hall: Without hall sensor (Standard)  
Steel/IP: Std. steel, Harsh Env.  
Brackets: AISI316 w/clevis  
Tube color: Black, RAL9005, shine 25 (Standard)  
Ring color: Black std. steel (IP68)  
Length: 1004 mm