



concens 
 member of **Bansbach** group

Oddesundvej 1
 DK-6715 Esbjerg N
 Denmark

Phone: +4570111131
 Mail: Info@concens.com
 Web: www.concens.com

Concens Part No.:

350100-193217D920000

Creation Date:
 02-07-2026

Sheet size:
 A4

Proprietary and confidential

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

Comments:

DIMENSIONS ARE IN mm,
 TOLERANCE ON DIMENSIONS CAN
 BE FOUND ON DATASHEET. OUT-OF-
 SCALE TECHNICAL DRAWING.

Configuration List:

- Stroke length: 100 mm
- Rod position: 0 mm
- Noise reduction: standard (Standard)
- Gearing: 1:19-600 N (nominal)
- Voltage: 24 VDC 1:19 (600N - 12mm/s)
- Pitch: 2 mm std. (Standard)
- Cable length: 1 m
- Cable Type and Connector: Black shielded cable, Molex Minifit Jr. Connector (Shielded cable is not available for EN/ES60601)
- Controller/Hall: icon SPP D
- Steel/IP: Std. steel, Harsh Env.
- Brackets: Alu
- Tube color: Black, RAL9005, shine 25 (Standard)
- Ring color: Black std. steel (IP68)
- Length: 281 mm