



concens 

member of **Bansbach** group

Oddesundvej 1
DK-6715 Esbjerg N
Denmark

Phone: +4570111131
Mail: Info@concens.com
Web: www.concens.com

Proprietary and confidential

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

Concens Part No.:

350150-143230-459900

Creation Date:
23-06-2026

Sheet size:
A4

Comments:

DIMENSIONS ARE IN mm,
TOLERANCE ON DIMENSIONS CAN
BE FOUND ON DATASHEET. OUT-OF-
SCALE TECHNICAL DRAWING.

Configuration List:

- Stroke length: 150 mm
- Rod position: 0 mm
- Noise reduction: standard (Standard)
- Gearing: 1:14-400 N (nominal)
- Voltage: 24 VDC 1:14 (400N - 16mm/s)
- Pitch: 2 mm std. (Standard)
- Cable length: 3 m
- Cable Type and Connector: Black, no connector
- Controller/Hall: Without hall sensor (Standard)
- Steel/IP: AISI316, Harsh Env.
- Brackets: AISI316 w/clevis
- Tube color: AISI316 (Standard)
- Ring color: AISI316 (Standard)
- Length: 331 mm