




concens 
 member of **Bansbach** group
 Oddesundvej 1 Phone: +4570111131
 DK-6715 Esbjerg N Mail: Info@concens.com
 Denmark Web: www.concens.com

Proprietary and confidential

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

Concens Part No.:

350200-271212+000000

Creation Date:

31-08-2026

Sheet size:

A4

Comments:

DIMENSIONS ARE IN mm,
 TOLERANCE ON DIMENSIONS CAN
 BE FOUND ON DATASHEET. OUT-OF-
 SCALE TECHNICAL DRAWING.

Configuration List:

Stroke length: 200 mm
 Rod position: 0 mm
 Noise reduction: standard (Standard)
 Gearing: 1:27-900 N (nominel)
 Voltage: 12 VDC 1:27 (900N - 7.5mm/s)
 Pitch: 2 mm std. (Standard)
 Cable length: 1 m
 Cable Type and Connector: Black, Molex Minifit (Standard)
 Controller/Hall: With hall sensor
 Steel/IP: Std. steel, IP66
 Brackets: PA
 Tube color: Black, RAL9005, shine 25 (Standard)
 Ring color: Black (Standard)
 Length: 370 mm