




concens 

member of **Bansbach** group

Oddesundvej 1
DK-6715 Esbjerg N
Denmark

Phone: +4570111131
Mail: Info@concens.com
Web: www.concens.com

Concens Part No.:
500200-493350-459900

Creation Date:
07-10-2026

Sheet size:
A4

Proprietary and confidential

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

Comments:

DIMENSIONS ARE IN mm,
TOLERANCE ON DIMENSIONS CAN
BE FOUND ON DATASHEET. OUT-OF-
SCALE TECHNICAL DRAWING.

Configuration List:

Stroke length: 200 mm
Rod position: 0 mm
Noise reduction: standard (Standard)
Gearing: 1:49-4500 N (nominel)
Voltage: 24 VDC 1:49 (4500N - 6mm/s)
Pitch: 3 mm std. (Standard)
Cable length: 5 m
Cable Type and Connector: Black, no connector
Controller/Hall: Without hall sensor (Standard)
Steel/IP: AISI316, Harsh Env.
Brackets: AISI316 w/clevis
Tube color: AISI316 (Standard)
Ring color: AISI316 (Standard)
Length: 469 mm