



concens 
 member of **Bansbach** group
 Oddesundvej 1 Phone: +4570111131
 DK-6715 Esbjerg N Mail: Info@concens.com
 Denmark Web: www.concens.com

Proprietary and confidential

The information contained in this drawing is the sole property of Concens A/S. Any reproduction in part or as a whole without the written permission of Concens A/S is prohibited.

Concens Part No.:

500400-843396F940200

Creation Date:
04-02-2026

Sheet size:
A4

Comments:

DIMENSIONS ARE IN mm,
TOLERANCE ON DIMENSIONS CAN
BE FOUND ON DATASHEET. OUT-OF-
SCALE TECHNICAL DRAWING.

Configuration List:

Stroke length: 400 mm
 Rod position: 0 mm
 Noise reduction: standard (Standard)
 Gearing: 1:84-4500 N (nominel)
 Voltage: 24 VDC 1:84 (4500N - 4mm/s)
 Pitch: 3 mm std. (Standard)
 Cable length: 9 m
 Cable Type and Connector: Black shielded cable, no connector (Shielded cable is not available for EN/ES60601)
 Controller/Hall: icon MDO F
 Steel/IP: Std. steel, Harsh Env.
 Brackets: AISI316
 Tube color: Black, RAL9005, shine 25 (Standard)
 Ring color: Black std. steel (IP68)
 Length: 684 mm